



New!

INSULATION PIERCING CONNECTORS - IPC

Galvan IPC Series connectors are an easy fit in copper-to-copper, copper-to-aluminum and aluminum-to-aluminum applications. Designed for splice or tap use, these units are not recommended for use with extra-flexible cables. The connectors are fully insulated and safe to install without special tools. IPC connectors eliminate time spent on wire stripping, taping and covers.

Insulation piercing connectors

- Wire range: #14 AWG to 750 MCM
- Versatile and reliable
- Use only with insulated conductors
- Installs without tape, stripping or cover
- Easy one-person installation
- UL 486B listed
- Rated: 600 volts, 90° C

Catalog Number	Conductor Range		No. of Bolts	Pieces Per Carton	Weight Per Carton
	Main AWG	Tap AWG			
IPC-1/0-2	1/0-8	2-10	1	6	30
IPC-1/0-1/0	1/0-8	1/-8	1	6	30
IPC-2/0-10	2/0-4	10-14	1	6	23
IPC-4/0-2	4/0-3	2-10	1	6	26
IPC-4/0-20	4/0-2	2/ 0-6	1	4	41
IPC-4/0-4/0	4/0-2	4/0-4	1	4	43
IPC-350-350	350-1/0	350-1/0	2	2	111
IPC-500-4/0	500-2/0	4/0-4	2	2	116
IPC-500-350	500-4/0	350-1/0	2	2	111
IPC-750-10	750-3/0	10-14	1	6	35
IPC-750-500	750-250	500-250	2	2	166

